MLCP PRESS FITTINGS

MLCP Press Radiator Elbow 16mm x 15mm with Pipe

16mm press elbow with 15mm radiator tail.

A 16mm U-profile MLCP press elbow with a 15mm radiator pipe already fitted. Bring a 16mm circuit up through the floor or out of the wall and go straight into a 15mm compression radiator valve.

CODES

MHF5-L1216x15S to MHF5-L1216x15CU-300



01 · KEY FEATURES

Why installers use it

- **Fewer joints at the radiator.** The elbow and the 15mm tail are one piece.
- **Fits standard valves.** Connects to any 15mm compression radiator valve. Cut the pipe to length as needed.
- **Press end.** 16mm MLCP, U-profile, with a brass body, stainless press sleeve and EPDM O-rings.
- **Rated.** Maximum working pressure 10 bar and maximum continuous temperature 80°C.

IN THE BOX

1 radiator elbow with pipe fitted

16 mm	10 bar	80 °C
PRESS END, MLCP, U-PROFILE	MAX WORKING PRESSURE	MAX TEMPERATURE, CONTINUOUS

02 · SPECIFICATION

Technical data

Press end	16mm MLCP, U-profile
Tail	15mm pipe, chrome-plated or plain copper
Tail length	150mm or 300mm
Body	Brass
Press sleeve	Stainless steel
Seals	EPDM O-rings
Max working pressure	10 bar
Max temperature	80°C continuous
Connects to	Any 15mm compression radiator valve

03 · DESIGN HELP

Send us your plans

For design help, send your plans to **sales@maxheatufh.com** or plan loops with **MaxHeatUFH ProLoop** at maxheatufh.com.

04 · SIZES AND CODES

Pick the size, one code each.

3 options by version. Order by code.

VERSION	CODE
Chrome, 150mm pipe	MHF5-L1216x15S-150
Chrome, 300mm pipe	MHF5-L1216x15S
Copper, 300mm pipe	MHF5-L1216x15CU-300

05 · WORKS WITH

Complete the system



U-Profile Press Jaws in 16mm



PERT-AL-PERT Multilayer Pipe



MLCP Press Fit Equal Elbow

ALSO WORKS WITH

U-Profile Press Jaws (16mm)

06 · FITTING AT A GLANCE

Full steps in the install manual

1. Cut the 16mm pipe square, then calibrate and bevel the bore with a Pipe Reaming Tool or Pipe Chamfering Tool.
2. Push the pipe fully home until it shows in the inspection window.
3. Press with the 16mm U-profile jaw.
4. Measure to the radiator valve and cut the 15mm tail square. Pick 150mm for a valve close to the floor or wall, 300mm where it sits higher.

07 · QUESTIONS

Asked by installers

Can I buy just one?

Yes. Unlike most of our MLCP fittings, these are sold singly.

Which pipe length should I pick?

150mm suits a valve close to the floor or wall. 300mm gives you more to cut down where the valve sits higher.

08 · GOOD TO KNOW

Versions

Sold individually: our supplier packs these singly.

SCAN ME

Watch how it works and fits

Point your phone camera at the code to watch the video for this product.

DESIGN HELP, TRADE ACCOUNTS AND ORDERS

sales@maxheatufh.com 07539 499069

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery