MLCP PRESS FITTINGS

MLCP Press Radiator Elbow 16mm x 15mm with Pipe

16mm press elbow with 15mm radiator tail.

A 16mm U-profile MLCP press elbow with a 15mm radiator pipe already fitted. Bring a 16mm circuit up through the floor or out of the wall and go straight into a 15mm compression radiator valve.

CODES

MHF5-L1216x15S to MHF5-L1216x15CU-300

PRODUCT



01 · IN THE BOX

What you get

- 1 radiator elbow with pipe fitted

02 · YOU WILL NEED

Tools and materials

- Multilayer pipe cutter
- Pipe Reaming Tool or Pipe Chamfering Tool
- Press tool with a 16mm U-profile jaw
- Pipe cutter for the 15mm tail
- Spanners

03 · SAFETY

Before you start

- Installation should be carried out by a competent installer, in line with the system design and current water and heating regulations.
- Isolate, drain and release the pressure before cutting into or working on a filled system.
- Use only the press jaw profile and size made for the fitting, and check every joint is pressed before filling.

04 · INSTALLATION

Fit it in 5 steps.

1. Cut the 16mm pipe square, then calibrate and bevel the bore with a Pipe Reaming Tool or Pipe Chamfering Tool.
2. Push the pipe fully home until it shows in the inspection window.
3. Press with the 16mm U-profile jaw.
4. **Measure to the radiator valve and cut the 15mm tail square.** Pick 150mm for a valve close to the floor or wall, 300mm where it sits higher.
5. Deburr the tail and connect it to the 15mm compression radiator valve.

05 · TESTING AND COMMISSIONING

Test, check, then hand over

- [x] Check the press joint and the valve nut for weeps during the pressure test.

06 · CARE AND MAINTENANCE

Keep it working

- Press joints are permanent. To change one, cut it out and fit a new elbow.

07 · GOOD TO KNOW

Versions

Sold individually: our supplier packs these singly.

08 · QUESTIONS

Asked by installers

Can I buy just one?

Yes. Unlike most of our MLCP fittings, these are sold singly.

Which pipe length should I pick?

150mm suits a valve close to the floor or wall. 300mm gives you more to cut down where the valve sits higher.

09 · WORKS WITH

Parts that fit with it



U-Profile Press Jaws in 16mm



PERT-AL-PERT Multilayer Pipe



MLCP Press Fit Equal Elbow

ALSO WORKS WITH

U-Profile Press Jaws (16mm)

10 · JOB RECORD

Fill in on site, keep for the handover

Site / room

Installed by

Date

Test result

Notes

SCAN ME

Watch how it works and fits

Point your phone camera at the code to watch the video.

QUESTIONS ON SITE?

sales@maxheatufh.com **07539 499069**

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery