COPPER M-PRESS FITTING PACKS

# Copper M-Press 15mm Fitting Pack (160 Fittings)

## 15mm radiator, hot and cold runs covered.

Covers 15mm radiator, hot and cold water runs in one order. Alongside couplings, elbows and tees it adds elbows i/a and 45° bends for tight turns, 22-15mm reducers, end caps for blanking, and 1/2" female tees and wall plated elbows for taps and outlets. 160 fittings as 15 full bags.

CODE
**MHF9-KIT15-160**




01 · KEY FEATURES

### Why installers use it

- **160 fittings across 9 lines,** all 15mm work from one box
- Elbows i/a and 45° bends for tight turns and offsets
- Female tees and wall plated elbows for taps and outlets
- Copper fittings with M-profile press ends: no flame, no solder
- **Supplied as 15 full bags**

IN THE BOX

15 full bags of copper M-press fittings (see the contents table on the data sheet)

02 · SPECIFICATION

### Technical data

| | |
|---|---|
| Contents | 160 fittings, 15 full bags |
| Size | 15mm (plus 22-15mm reducers and 1/2" threads) |
| Press profile | M-profile |
| Pipe | Copper tube |
| Jaws (MaxHeatUFH) | 15mm fits MH-EHCS and MH-HPEHCS |
| Packs | Supplied as full bags, not split |

03 · DESIGN HELP

### Send us your plans

For design help, send your plans to **sales@maxheatufh.com** or plan loops with **MaxHeatUFH ProLoop** at maxheatufh.com.

04 · ORDER CODE

# MHF9-KIT15-160.

One code for this product. Check the specification on page 1 before you order.

05 · PACK CONTENTS

## Pack contents

| FITTING | SIZE | QTY |
|---|---|---|
| Equal Straight Coupling | 15mm | 20 |
| Equal Elbow | 15mm | 30 |
| Equal Tee | 15mm | 20 |
| Fitting Reducer | 22-15mm | 20 |
| Elbow i/a | 15mm | 10 |
| Equal 45 Bend | 15mm | 20 |
| End Cap | 15mm | 20 |
| Female Tee | 15mm x 1/2" x 15mm | 10 |
| Female Wall Plated Elbow | 15mm x 1/2" | 10 |

Total 160 fittings. All lines are Copper M-Press.

06 · WORKS WITH

## Complete the system

- MaxHeatUFH M-Profile Press Jaws
- Electric Hydraulic Press Tool Set (MH-EHCS)
- High Power Electric Hydraulic Press Tool (MH-HPEHCS)
- Copper M-Press 22mm Fitting Pack for the larger runs

07 · FITTING AT A GLANCE

## Full steps in the install manual

1. Check the pack: 15 bags, 160 fittings, against the contents table.
2. Cut the copper tube square and deburr inside and out.
3. Mark the insertion depth, then push the fitting on fully to the mark.
4. Press each joint with the 15mm M-profile jaw, square over the fitting bead, until the tool completes its cycle.

SCAN ME

## Watch how it works and fits

Point your phone camera at the code to watch the video for this product.

DESIGN HELP, TRADE ACCOUNTS AND ORDERS

**sales@maxheatufh.com** **07539 499069**

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery