COPPER M-PRESS FITTING PACKS

Copper M-Press 22mm Fitting Pack (90 Fittings)
For 22mm flow, return, primary and mains runs.

Built for 22mm flow and return, primary and mains runs. Couplings, elbows and equal tees, plus elbows i/a and 45° bends for tight turns, 22-22-15mm tees for 15mm branches, and end caps for blanking and pressure testing. 90 fittings as 9 full bags.

CODE
MHF9-KIT22-90



01 · KEY FEATURES

Why installers use it

- 90 fittings across 7 lines for 22mm pipework
- Unequal tees take a 15mm branch straight off the 22mm run
- End caps for blanking and pressure testing
- Copper fittings with M-profile press ends: no flame, no solder
- **Supplied as 9 full bags**

IN THE BOX

9 full bags of copper M-press fittings (see the contents table on the data sheet)

02 · SPECIFICATION

Technical data

Contents	90 fittings, 9 full bags
Size	22mm (plus 22-22-15mm branch tees)
Press profile	M-profile
Pipe	Copper tube
Jaws (MaxHeatUFH)	15mm and 22mm fit MH-EHCS and MH-HPEHCS
Packs	Supplied as full bags, not split

03 · DESIGN HELP

Send us your plans

For design help, send your plans to **sales@maxheatufh.com** or plan loops with **MaxHeatUFH ProLoop** at maxheatufh.com.

04 · ORDER CODE

MHF9-KIT22-90.

One code for this product. Check the specification on page 1 before you order.

05 · PACK CONTENTS

Pack contents

FITTING	SIZE	QTY
Equal Straight Coupling	22mm	20
Equal Elbow	22mm	20
Equal Tee	22mm	10
Elbow i/a	22mm	10
Equal 45 Bend	22mm	10
Unequal Tee	22-22-15mm	10
End Cap	22mm	10

Total 90 fittings. All lines are Copper M-Press.

06 · WORKS WITH

Complete the system

- MaxHeatUFH M-Profile Press Jaws
- Electric Hydraulic Press Tool Set (MH-EHCS)
- High Power Electric Hydraulic Press Tool (MH-HPEHCS)
- Copper M-Press 15mm Fitting Pack for the smaller runs

07 · FITTING AT A GLANCE

Full steps in the install manual

1. Check the pack: 9 bags, 90 fittings, against the contents table.
2. Cut the copper tube square and deburr inside and out.
3. Mark the insertion depth, then push the fitting on fully to the mark.
4. Press each joint with the matching M-profile jaw, square over the fitting bead, until the tool completes its cycle.

SCAN ME

Watch how it works and fits

Point your phone camera at the code to watch the video for this product.

DESIGN HELP, TRADE ACCOUNTS AND ORDERS

sales@maxheatufh.com **07539 499069**

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery