COPPER M-PRESS FITTINGS

Copper M-Press End Cap
Seals a copper tube end.

Seals the end of a copper tube with one press. Cap off a dead leg, blank a spur for later, or close a run for a pressure test.

CODES

MHF9-D15-BAG20 to MHF9-D54-BOX20



01 · KEY FEATURES

Why installers use it

- **Quick blanking.** One press and the tube is sealed.
- **Every size.** 15, 22, 28, 35, 42 and 54mm.
- **Bigger bags.** 15mm comes in bags of 20 and boxes of 300.
- **Full packs.** Bag or box. Our supplier does not split packs.

IN THE BOX

Fittings in a full bag or box (quantity is in the code, e.g. BAG10 = 10)

02 · SPECIFICATION

Technical data

Type	Press end cap
Press profile	M-profile
Pipe	Copper tube
Jaws (MaxHeatUFH)	15, 22, 28mm: MH-EHCS or MH-HPEHCS. 35, 42, 54mm: MH-HPEHCS only
Packs	Full bags or boxes, not split

03 · QUESTIONS

Asked by installers

Which press tool do I need?

Any tool that takes M-profile jaws in the size you are pressing. With MaxHeatUFH jaws, 15, 22 and 28mm fit both the Electric Hydraulic Press Tool (MH-EHCS) and the High Power tool (MH-HPEHCS). 35, 42 and 54mm need the High Power tool.

Can I buy single fittings?

No. Our supplier does not split packs, so we sell full bags and boxes only.

04 · DESIGN HELP

Send us your plans

For design help, send your plans to **sales@maxheatufh.com** or plan loops with **MaxHeatUFH ProLoop** at maxheatufh.com.

05 · SIZES AND CODES

Pick the size, one code each.

12 options by size, pack. Order by code.

SIZE	BAG CODE	BOX CODE
15mm	MHF9-D15-BAG20	MHF9-D15-BOX300
22mm	MHF9-D22-BAG10	MHF9-D22-BOX180
28mm	MHF9-D28-BAG10	MHF9-D28-BOX120
35mm	MHF9-D35-BAG5	MHF9-D35-BOX60
42mm	MHF9-D42-BAG5	MHF9-D42-BOX30
54mm	MHF9-D54-BAG5	MHF9-D54-BOX20

06 · PACK SIZES

SIZE	BAG	BOX
15mm	20	300
22mm	10	180
28mm	10	120
35mm	5	60
42mm	5	30
54mm	5	20

07 · WORKS WITH

Complete the system



Copper M-Press Equal Tee



Copper M-Press Lever Ball Valve



MaxHeatUFH M-Profile Press Jaws and M-Profile Angled Press Jaws

ALSO WORKS WITH

MaxHeatUFH M-Profile and Angled Press Jaws

08 · FITTING AT A GLANCE

Full steps in the install manual

1. Cut the tube square with a tube cutter.
2. Deburr the tube end inside and out and wipe it clean.
3. Mark the insertion depth on the tube.
4. Check the seal is seated in the socket and undamaged.

SCAN ME

Watch how it works and fits

Point your phone camera at the code to watch the video for this product.

DESIGN HELP, TRADE ACCOUNTS AND ORDERS

sales@maxheatufh.com **07539 499069**

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery