COPPER M-PRESS FITTINGS

Copper M-Press Equal 45 Bend i/a
45° bend, press x spigot.

A 45° bend with a press socket at one end and a spigot at the other. Push the spigot into another press fitting for a compact offset with no short length of tube.

CODES
MHF9-Bi/a15x15-BOX150 to MHF9-Bi/a54x54-BOX6



01 · KEY FEATURES

Why installers use it

- **Compact offsets.** Fit it straight into an elbow, tee or coupling.
- **Fewer cuts.** No short pieces of tube to cut, deburr and press.
- **M-profile press.** Flame-free with the matching M-profile jaw.
- **Box only.** This fitting is not sold in bags. Our supplier does not split boxes.

IN THE BOX

Fittings in a full bag or box (quantity is in the code, e.g. BAG10 = 10)

02 · SPECIFICATION

Technical data

Ends	Press socket x spigot (i/a), 45°
Press profile	M-profile
Pipe	Copper tube
Jaws (MaxHeatUFH)	15, 22, 28mm: MH-EHCS or MH-HPEHCS. 35, 42, 54mm: MH-HPEHCS only
Packs	Full bags or boxes, not split

03 · QUESTIONS

Asked by installers

Is there a bag option?

No. The 45° bend i/a comes in full boxes only. If you need smaller numbers, the standard 45° bend comes in bags.

What does i/a mean?

One end is a press socket for tube and the other is a spigot that goes into another press fitting.

04 · DESIGN HELP

Send us your plans

For design help, send your plans to **sales@maxheatufh.com** or plan loops with **MaxHeatUFH ProLoop** at maxheatufh.com.

05 · SIZES AND CODES

Pick the size, one code each.

6 options by size, pack. Order by code.

SIZE	BOX CODE
15mm	MHF9-Bi/a15x15-BOX150
22mm	MHF9-Bi/a22x22-BOX80
28mm	MHF9-Bi/a28x28-BOX40
35mm	MHF9-Bi/a35x35-BOX20
42mm	MHF9-Bi/a42x42-BOX12
54mm	MHF9-Bi/a54x54-BOX6

06 · PACK SIZES

SIZE	BOX
15mm	150
22mm	80
28mm	40
35mm	20
42mm	12
54mm	6

07 · WORKS WITH

Complete the system



Copper M-Press Equal 45 Bend (press both ends)



Copper M-Press Elbow i/a



MaxHeatUFH M-Profile Press Jaws

08 · FITTING AT A GLANCE

Full steps in the install manual

1. Cut the tube square with a tube cutter.
2. Deburr the tube end inside and out and wipe it clean.
3. Mark the insertion depth on the tube.
4. Check the seal is seated in the socket and undamaged.

SCAN ME

Watch how it works and fits

Point your phone camera at the code to watch the video for this product.

DESIGN HELP, TRADE ACCOUNTS AND ORDERS

sales@maxheatufh.com **07539 499069**

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery