COPPER M-PRESS FITTINGS

Copper M-Press Equal Sleeve Coupling
Equal coupling, 15 to 54mm.

An equal coupling for joining copper tube of the same size, pressed cold with M-profile jaws. Pack quantities are in the product code, so check the table before ordering.

CODES

MHF9-SLC15x15-BAG10 to MHF9-SLC54x54-BOX8



01 · KEY FEATURES

Why installers use it

- **Cold pressed joint.** No flame or solder, just an M-profile press tool and the right jaw.
- **Full size range.** 15, 22, 28, 35, 42 and 54mm.
- **Different pack counts.** The quantity is in the code, so check the table before you order.
- **Full packs only.** Sold by the bag or box. Our supplier does not split packs.

IN THE BOX

Fittings in a full bag or box (quantity is in the code, e.g. BAG10 = 10)

02 · SPECIFICATION

Technical data

Ends	Press x press, equal
Sizes	15, 22, 28, 35, 42, 54mm
Press profile	M-profile
Pipe	Copper tube
Jaws (MaxHeatUFH)	15, 22, 28mm: MH-EHCS or MH-HPEHCS. 35, 42, 54mm: MH-HPEHCS only
Packs	Full bags or boxes, not split

03 · QUESTIONS

Asked by installers

Straight coupling or sleeve coupling?

Both join tube of the same size in line. If you are not sure which suits your job, contact us before you order.

Is it sold singly?

No. It comes in full bags or boxes only, as our supplier does not split packs.

04 · DESIGN HELP

Send us your plans

For design help, send your plans to **sales@maxheatufh.com** or plan loops with **MaxHeatUFH ProLoop** at maxheatufh.com.

05 · SIZES AND CODES

Pick the size, one code each.

12 options by size, pack. Order by code.

SIZE	BAG CODE	BOX CODE
15mm	MHF9-SLC15x15-BAG10	MHF9-SLC15x15-BOX100
22mm	MHF9-SLC22x22-BAG10	MHF9-SLC22x22-BOX50
28mm	MHF9-SLC28x28-BAG5	MHF9-SLC28x28-BOX40
35mm	MHF9-SLC35x35-BAG5	MHF9-SLC35x35-BOX25
42mm	MHF9-SLC42x42-BAG2	MHF9-SLC42x42-BOX12
54mm	MHF9-SLC54x54-BAG2	MHF9-SLC54x54-BOX8

06 · PACK SIZES

SIZE	BAG	BOX
15mm	10	100
22mm	10	50
28mm	5	40
35mm	5	25
42mm	2	12
54mm	2	8

07 · WORKS WITH

Complete the system



MaxHeatUFH M-Profile Press Jaws for 15 to 28mm, or M-Profile Angled Press Jaws for the High Power tool



Copper M-Press Equal Straight Coupling

ALSO WORKS WITH

- MaxHeatUFH M-Profile Press Jaws (15 to 28mm)
- M-Profile Angled Press Jaws (High Power tool)

08 · FITTING AT A GLANCE

Full steps in the install manual

1. Cut the tube square with a tube cutter.
2. Deburr the tube end inside and out and wipe it clean.
3. Mark the insertion depth on the tube.
4. Check the seal is seated in the socket and undamaged.

SCAN ME

Watch how it works and fits

Point your phone camera at the code to watch the video for this product.

DESIGN HELP, TRADE ACCOUNTS AND ORDERS

sales@maxheatufh.com **07539 499069**

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery