COPPER M-PRESS FITTINGS

Copper M-Press Equal Straight Coupling
Straight joint, 15 to 54mm.

Joins two lengths of the same size copper tube in a straight line. One of our best-selling copper press fittings, pressed cold with an M-profile jaw.

CODES

MHF9-SC15x15-BAG10 to MHF9-SC54x54-BOX12



01 · KEY FEATURES

Why installers use it

- **Flame-free joints.** Press each end with an M-profile press tool and the matching jaw.
- **Six sizes.** 15, 22, 28, 35, 42 and 54mm, all equal both ends.
- **Packs for every job.** A bag for the van or a box for bigger runs. Our supplier does not split packs.

IN THE BOX

Fittings in a full bag or box (quantity is in the code, e.g. BAG10 = 10)

02 · SPECIFICATION

Technical data

Ends	Press x press, equal
Sizes	15, 22, 28, 35, 42, 54mm
Press profile	M-profile
Pipe	Copper tube
Jaws (MaxHeatUFH)	15, 22, 28mm: MH-EHCS or MH-HPEHCS. 35, 42, 54mm: MH-HPEHCS only
Packs	Full bags or boxes, not split

03 · QUESTIONS

Asked by installers

Which press tool do I need?

Any tool that takes M-profile jaws in the size you are pressing. With MaxHeatUFH jaws, 15, 22 and 28mm fit both the Electric Hydraulic Press Tool (MH-EHCS) and the High Power tool (MH-HPEHCS). 35, 42 and 54mm need the High Power tool.

Can I buy single fittings?

No. Our supplier does not split packs, so we sell full bags and boxes only.

04 · SIZES AND CODES

Pick the size, one code each.

12 options by size, pack. Order by code.

SIZE	BAG CODE	BOX CODE
15mm	MHF9-SC15x15-BAG10	MHF9-SC15x15-BOX180
22mm	MHF9-SC22x22-BAG10	MHF9-SC22x22-BOX90
28mm	MHF9-SC28x28-BAG10	MHF9-SC28x28-BOX60
35mm	MHF9-SC35x35-BAG5	MHF9-SC35x35-BOX25
42mm	MHF9-SC42x42-BAG2	MHF9-SC42x42-BOX20
54mm	MHF9-SC54x54-BAG2	MHF9-SC54x54-BOX12

05 · PACK SIZES

SIZE	BAG	BOX
15mm	10	180
22mm	10	90
28mm	10	60
35mm	5	25
42mm	2	20
54mm	2	12

06 · WORKS WITH

Complete the system



MaxHeatUFH M-Profile Press Jaws and the Electric Hydraulic Press Tool Set



Copper M-Press Equal Sleeve Coupling



Copper M-Press Straight Reducer

07 · FITTING AT A GLANCE

Full steps in the install manual

1. Cut the tube square with a tube cutter.
2. Deburr the tube end inside and out and wipe it clean.
3. Mark the insertion depth on the tube.
4. Check the seal is seated in the socket and undamaged.

08 · DESIGN HELP

Send us your plans

For design help, send your plans to **sales@maxheatufh.com** or plan loops with **MaxHeatUFH ProLoop** at maxheatufh.com.

SCAN ME

Watch how it works and fits

Point your phone camera at the code to watch the video for this product.

DESIGN HELP, TRADE ACCOUNTS AND ORDERS

sales@maxheatufh.com **07539 499069**

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery