COPPER M-PRESS FITTINGS

Copper M-Press Equal Tee
Same size on all three ends.

Takes a branch off a copper run with all three ends the same size, for splitting heating flow and return or feeding taps and appliances.

CODES

MHF9-T15x15x15-BAG10 to MHF9-T54x54x54-BOX4



01 · KEY FEATURES

Why installers use it

- **Three equal ends.** 15, 22, 28, 35, 42 or 54mm on every port.
- **Quick to fit.** Three presses and the branch is done, with no solder to clean up.
- **Works with the range.** Add a reducer or use an unequal tee when the branch needs to change size.
- **Full packs.** Bag or box. 54mm is box only.

IN THE BOX

Fittings in a full bag or box (quantity is in the code, e.g. BAG10 = 10)

02 · SPECIFICATION

Technical data

Ends	Press x press x press, equal
Press profile	M-profile
Pipe	Copper tube
Jaws (MaxHeatUFH)	15, 22, 28mm: MH-EHCS or MH-HPEHCS. 35, 42, 54mm: MH-HPEHCS only
Packs	Full bags or boxes, not split

03 · QUESTIONS

Asked by installers

I need a smaller branch. What should I buy?

Use the unequal tee, which comes in 26 size combinations.

Can I buy single fittings?

No. Our supplier does not split packs, so we sell full bags and boxes only.

04 · DESIGN HELP

Send us your plans

For design help, send your plans to **sales@maxheatufh.com** or plan loops with **MaxHeatUFH ProLoop** at maxheatufh.com.

05 · SIZES AND CODES

Pick the size, one code each.

11 options by size, pack. Order by code.

SIZE	BAG CODE	BOX CODE
15mm	MHF9-T15x15x15-BAG10	MHF9-T15x15x15-BOX80
22mm	MHF9-T22x22x22-BAG10	MHF9-T22x22x22-BOX40
28mm	MHF9-T28x28x28-BAG5	MHF9-T28x28x28-BOX25
35mm	MHF9-T35x35x35-BAG2	MHF9-T35x35x35-BOX12
42mm	MHF9-T42x42x42-BAG2	MHF9-T42x42x42-BOX8
54mm		MHF9-T54x54x54-BOX4

06 · PACK SIZES

SIZE	BAG	BOX
15mm	10	80
22mm	10	40
28mm	5	25
35mm	2	12
42mm	2	8
54mm	-	4

07 · WORKS WITH

Complete the system



Copper M-Press Unequal Tee



Copper M-Press Female Tee



MaxHeatUFH M-Profile Press Jaws and the Electric Hydraulic Press Tool Set

08 · FITTING AT A GLANCE

Full steps in the install manual

1. Cut the tube square with a tube cutter.
2. Deburr the tube end inside and out and wipe it clean.
3. Mark the insertion depth on the tube.
4. Check the seal is seated in the socket and undamaged.

SCAN ME

Watch how it works and fits

Point your phone camera at the code to watch the video for this product.

DESIGN HELP, TRADE ACCOUNTS AND ORDERS

sales@maxheatufh.com 07539 499069

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery