COPPER M-PRESS FITTINGS

Copper M-Press Female Elbow
90° tube to female thread.

Turns 90° from copper tube to a female thread. Press the tube end and screw a male part, such as a valve, drain cock or appliance connection, into the other.

CODES

MHF9-L15x1/2F-BAG10 to MHF9-L28x1F-BOX35

PRODUCT



01 · IN THE BOX

What you get

- Fittings in a full bag or box (quantity is in the code, e.g. BAG10 = 10)

02 · YOU WILL NEED

Tools and materials

- Tube cutter
- Deburring tool
- Marker pen
- Press tool with M-profile jaws
- Thread sealant

03 · SAFETY

Before you start

- Installation should be carried out by a competent installer, in line with the system design and current water and heating regulations.
- Isolate, drain and release the pressure before cutting into or working on a filled system.
- Use only the press jaw profile and size made for the fitting, and check every joint is pressed before filling.

04 · INSTALLATION

Fit it in 8 steps.

1. Cut the tube square with a tube cutter.
2. Deburr the tube end inside and out and wipe it clean.
3. Mark the insertion depth on the tube.
4. Check the seal is seated in the socket and undamaged.
5. **Seal the threaded end in the normal way for a threaded joint.** Only the tube end is pressed.
6. Push the tube in up to the mark.
7. Fit the M-profile jaw of the same size, place it square over the fitting bead and run a full press cycle.
8. Check the mark still sits at the fitting edge, so the tube did not move while pressing.

05 · TESTING AND COMMISSIONING

Test, check, then hand over

- ☑ Before filling, check every joint has been pressed.
- ☑ Pressure test to the system design and check each joint for weeps.

06 · CARE AND MAINTENANCE

Keep it working

- Pressed joints are permanent. To change one, cut it out and fit a new fitting.

07 · PACK SIZES

SIZE	BAG	BOX
15mm x 1/2"	10	100
22mm x 3/4"	5	60
28mm x 1"	5	35

08 · QUESTIONS

Asked by installers

Which end do I press?
Only the tube end. The threaded end is sealed in the normal way for a threaded joint.

Can I buy single fittings?
No. Our supplier does not split packs, so we sell full bags and boxes only.

09 · WORKS WITH

Parts that fit with it



Copper M-Press Male Elbow



Copper M-Press Female Wall Plated Elbow



Copper M-Press Female Straight

SCAN ME

Watch how it works and fits

Point your phone camera at the code to watch the video.

QUESTIONS ON SITE?

sales@maxheatufh.com **07539 499069**

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery