COPPER M-PRESS FITTINGS

# Copper M-Press Female Wall Plated Elbow 15mm x 1/2" Fixed tap and shower outlet.

An elbow with a fixing plate that screws firmly to a wall or noggin. Press 15mm copper into it and connect a 1/2" male thread, such as a tap or shower valve, to the female outlet.

CODES

**MHF9-L15x1/2FZ-BAG10 to MHF9-L15x1/2FZ-BOX70**

PRODUCT



01 · IN THE BOX

## What you get

- Fittings in a full bag or box (quantity is in the code, e.g. BAG10 = 10)

02 · YOU WILL NEED

## Tools and materials

- Tube cutter
- Deburring tool
- Marker pen
- Press tool with M-profile jaws
- Thread sealant

03 · SAFETY

## Before you start

- Installation should be carried out by a competent installer, in line with the system design and current water and heating regulations.
- Isolate, drain and release the pressure before cutting into or working on a filled system.
- Use only the press jaw profile and size made for the fitting, and check every joint is pressed before filling.

04 · INSTALLATION

## Fit it in 8 steps.

1. Cut the tube square with a tube cutter.
2. Deburr the tube end inside and out and wipe it clean.
3. Mark the insertion depth on the tube.
4. Check the seal is seated in the socket and undamaged.
5. **Seal the threaded end in the normal way for a threaded joint.** Only the tube end is pressed.
6. Push the tube in up to the mark.
7. Fit the M-profile jaw of the same size, place it square over the fitting bead and run a full press cycle.
8. Screw the plate firmly to the wall or noggin.

05 · TESTING AND COMMISSIONING

## Test, check, then hand over

- [x] Before filling, check every joint has been pressed.
- [x] Pressure test to the system design and check each joint for weeps.

06 · CARE AND MAINTENANCE

## Keep it working

- Pressed joints are permanent. To change one, cut it out and fit a new fitting.

07 · PACK SIZES

| SIZE | BAG | BOX |
|---|---|---|
| 15mm x 1/2" | 10 | 70 |

08 · QUESTIONS

## Asked by installers

**Can I buy just one or two?**

No. The smallest pack is a bag of 10, as our supplier does not split packs.

**Will my press tool do it?**

Yes, if it takes a 15mm M-profile jaw. Both MaxHeatUFH electric hydraulic tools do.

09 · WORKS WITH

## Parts that fit with it



Copper M-Press Female Elbow



Copper M-Press Tap Connector



MaxHeatUFH M-Profile Press Jaws and the Electric Hydraulic Press Tool Set

10 · JOB RECORD

## Fill in on site, keep for the handover

Site / room

Installed by

Date

Test result

Notes

SCAN ME

### Watch how it works and fits

Point your phone camera at the code to watch the video.

QUESTIONS ON SITE?

**sales@maxheatufh.com** **07539 499069**

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery