COPPER M-PRESS FITTINGS

Copper M-Press Tap Connector
Copper tube to tap tail.

Joins copper tube to a tap tail or other male threaded outlet. Press the tube end and do up the threaded end onto the tail.

CODES

MHF9-S15x1/2TC-BAG10 to MHF9-S28x1-1/4TC-BOX70



01 · KEY FEATURES

Why installers use it

- **Taps and outlets.** A quick tube to tail connection at basins, sinks and appliances.
- **Five sizes.** 15mm x 1/2", 15mm x 3/4", 22mm x 3/4", 22mm x 1" and 28mm x 1 1/4".
- **No flame under sinks.** Pressed cold, so no torch in tight cupboards.
- **Full packs.** Bag or box. Packs are not split.

IN THE BOX

Fittings in a full bag or box (quantity is in the code, e.g. BAG10 = 10)

02 · SPECIFICATION

Technical data

Sizes	Tube size first, then the thread on the tap tail
Press profile	M-profile
Pipe	Copper tube
Jaws (MaxHeatUFH)	15, 22, 28mm: MH-EHCS or MH-HPEHCS. 35, 42, 54mm: MH-HPEHCS only
Packs	Full bags or boxes, not split

03 · GOOD TO KNOW

Choosing the size

Match the first number to your copper tube and the second to the thread on the tap tail or outlet.

04 · QUESTIONS

Asked by installers

Will it work with my press tool?

Yes, if your tool takes M-profile jaws in 15, 22 or 28mm. Both MaxHeatUFH electric hydraulic tools do.

Can I buy single fittings?

No. Our supplier does not split packs, so we sell full bags and boxes only.

05 · SIZES AND CODES

Pick the size, one code each.

10 options by size, pack. Order by code.

SIZE	BAG CODE	BOX CODE
15mm x 1/2"	MHF9-S15x1/2TC-BAG10	MHF9-S15x1/2TC-BOX120
15mm x 3/4"	MHF9-S15x3/4TC-BAG10	MHF9-S15x3/4TC-BOX150
22mm x 3/4"	MHF9-S22x3/4TC-BAG10	MHF9-S22x3/4TC-BOX80
22mm x 1"	MHF9-S22x1TC-BAG10	MHF9-S22x1TC-BOX100
28mm x 1 1/4"	MHF9-S28x1-1/4TC-BAG5	MHF9-S28x1-1/4TC-BOX70

06 · PACK SIZES

SIZE	BAG	BOX
15mm x 1/2"	10	120
15mm x 3/4"	10	150
22mm x 3/4"	10	80
22mm x 1"	10	100
28mm x 1 1/4"	5	70

07 · WORKS WITH

Complete the system



Copper M-Press Female Wall Plated Elbow



Copper M-Press Lever Ball Valve



MaxHeatUFH M-Profile Press Jaws and the Electric Hydraulic Press Tool Set

08 · FITTING AT A GLANCE

Full steps in the install manual

1. Cut the tube square with a tube cutter.
2. Deburr the tube end inside and out and wipe it clean.
3. Mark the insertion depth on the tube.
4. Check the seal is seated in the socket and undamaged.

09 · DESIGN HELP

Send us your plans

For design help, send your plans to **sales@maxheatufh.com** or plan loops with **MaxHeatUFH ProLoop** at maxheatufh.com.

SCAN ME

Watch how it works and fits

Point your phone camera at the code to watch the video for this product.

DESIGN HELP, TRADE ACCOUNTS AND ORDERS

sales@maxheatufh.com **07539 499069**

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery