COPPER M-PRESS FITTINGS

Copper M-Press Tap Connector
Copper tube to tap tail.

Joins copper tube to a tap tail or other male threaded outlet. Press the tube end and do up the threaded end onto the tail.

CODES

MHF9-S15x1/2TC-BAG10 to MHF9-S28x1-1/4TC-BOX70

PRODUCT



01 · IN THE BOX

What you get

- Fittings in a full bag or box (quantity is in the code, e.g. BAG10 = 10)

02 · YOU WILL NEED

Tools and materials

- Tube cutter
- Deburring tool
- Marker pen
- Press tool with M-profile jaws
- Thread sealant

03 · SAFETY

Before you start

- Installation should be carried out by a competent installer, in line with the system design and current water and heating regulations.
- Isolate, drain and release the pressure before cutting into or working on a filled system.
- Use only the press jaw profile and size made for the fitting, and check every joint is pressed before filling.

04 · INSTALLATION

Fit it in 8 steps.

1. Cut the tube square with a tube cutter.
2. Deburr the tube end inside and out and wipe it clean.
3. Mark the insertion depth on the tube.
4. Check the seal is seated in the socket and undamaged.
5. **Seal the threaded end in the normal way for a threaded joint.** Only the tube end is pressed.
6. Push the tube in up to the mark.
7. Fit the M-profile jaw of the same size, place it square over the fitting bead and run a full press cycle.
8. Check the mark still sits at the fitting edge, so the tube did not move while pressing.

05 · TESTING AND COMMISSIONING

Test, check, then hand over

- [x] Before filling, check every joint has been pressed.
- [x] Pressure test to the system design and check each joint for weeps.

06 · CARE AND MAINTENANCE

Keep it working

- Pressed joints are permanent. To change one, cut it out and fit a new fitting.

07 · PACK SIZES

SIZE	BAG	BOX
15mm x 1/2"	10	120
15mm x 3/4"	10	150
22mm x 3/4"	10	80
22mm x 1"	10	100
28mm x 1 1/4"	5	70

08 · GOOD TO KNOW

Choosing the size

Match the first number to your copper tube and the second to the thread on the tap tail or outlet.

09 · QUESTIONS

Asked by installers

Will it work with my press tool?

Yes, if your tool takes M-profile jaws in 15, 22 or 28mm. Both MaxHeatUFH electric hydraulic tools do.

Can I buy single fittings?


No. Our supplier does not split packs, so we sell full bags and boxes only.

10 · WORKS WITH

Parts that fit with it



Copper M-Press Female Wall Plated Elbow



Copper M-Press Lever Ball Valve



MaxHeatUFH M-Profile Press Jaws and the Electric Hydraulic Press Tool Set

SCAN ME

Watch how it works and fits

Point your phone camera at the code to watch the video.

QUESTIONS ON SITE?

sales@maxheatufh.com **07539 499069**

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery