MANIFOLDS & COMPONENTS

Eurocone Connector Cores 3/4" Pipe connectors for 3/4" Eurocone outlets.

Connect underfloor heating and multilayer pipe to 3/4" Eurocone manifold outlets, splitters and adaptors. Each core is a nut, a split olive and a pipe insert. Choose the core that matches your pipe's outside diameter and wall thickness.

CODES

MHF1-C0710x3/4A to MHF1-C1620x3/4A

PRODUCT



01 · IN THE BOX

What you get

- 1 connector core: nut, split olive, pipe insert

02 · YOU WILL NEED

Tools and materials

- Pipe cutter
- Reaming tool
- Spanners

03 · SAFETY

Before you start

- Installation should be carried out by a competent installer, in line with the system design and BS EN 1264.
- Isolate and drain down, or isolate with the manifold ball valves, before working on a filled system.
- Hot water and pressure can cause injury. Let the system cool and release pressure before opening any joint.

04 · INSTALLATION

Fit it in 6 steps.

1. Check the size printed on the pipe (for example 16 x 2.0) and pick the core with the same figures.
2. Cut the pipe square with a pipe cutter and ream the end so the insert slides in cleanly.
3. Slide the nut, then the split olive, onto the pipe.
4. Push the insert fully into the pipe end.
5. Offer the pipe to the Eurocone outlet, push it home and tighten the nut by hand.
6. **Finish with a spanner.** Do not overtighten; hold the outlet steady so the manifold bar does not twist.

05 · TESTING AND COMMISSIONING

Test, check, then hand over

- [x] Check every core for weeps during the pressure test, and again once the system is up to temperature.

06 · CARE AND MAINTENANCE

Keep it working

- If a joint weeps, isolate, release pressure and re-make it with a new core.

07 · GOOD TO KNOW

How many do I need?

Two per circuit: one for the flow and one for the return. A 6 port manifold with six loops needs 12 cores.

08 · QUESTIONS

Asked by installers

How do I pick the right core?


Check the pipe's outside diameter and wall thickness, usually printed on the pipe, for example 16 x 2.0. Choose the core with the same figures.

Can I buy single cores?

Yes. They are sold individually.

09 · WORKS WITH

Parts that fit with it



Dualmix Stainless Steel Manifold



Auto-Balancing Stainless Steel UFH Manifold



PERT-AL-PERT Multilayer UFH Pipe



3-Layer PERT-EVOH UFH Pipe

ALSO WORKS WITH

PERT-EVOH UFH Pipe

SCAN ME

Watch how it works and fits

Point your phone camera at the code to watch the video.

QUESTIONS ON SITE?

sales@maxheatufh.com **07539 499069**

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery