HEATMISER CONTROLS

Heatmiser neoStat V3 Programmable Smart Thermostat 230V

The standard neo zone thermostat.

A 230V smart thermostat for UFH and radiator zones. Use it as a programmable thermostat or a dedicated timer, and add a neoHub (2nd generation or later) for control from the neoApp.

CODES

HM-NEOSTAT-V3-W, -B, -S



01 · KEY FEATURES

Why installers use it

- App control through the neoApp with a neoHub
- **Built-in air,** remote air or floor sensing: works with 10K, 12K and 15K NTC floor probes
- **Self-learning Optimum Start,** hold, holiday and frost protection
- Each mains neoStat also acts as a repeater in the neo mesh
- Backlit display with illuminated touch keys

IN THE BOX

neoStat V3 thermostat | Fixing screws

02 · SPECIFICATION

Technical data

Supply	230V AC
Max switching current	3A
Temperature range	5 to 35°C
Accuracy	±1°C
Programming	5/2 day, 7 day, 24 hour, or non-programmable

Size (L x H x D)	85 × 85 × 15mm
Back box	Fits a standard 35mm deep back box
Colours	Glacier White, Sapphire Black, Platinum Silver
Warranty	2 years
neoHub	2nd generation or later; not the 1st gen hub or neoHub Mini

03 · DESIGN HELP

Send us your plans

For design help, send your plans to **sales@maxheatufh.com** or plan loops with **MaxHeatUFH ProLoop** at maxheatufh.com.

04 · COLOURS AND CODES

Pick the colour, one code each.

3 options by colour. Order by code.

COLOUR	CODE
Glacier White	HM-NEOSTAT-V3-W
Sapphire Black	HM-NEOSTAT-V3-B
Platinum Silver	HM-NEOSTAT-V3-S

05 · WORKS WITH

Complete the system

- Heatmiser neoHub G3 for app control
- Heatmiser UH4 or UH8 Wiring Centre
- 10K Floor Probe (3m) for floor sensing

06 · FITTING AT A GLANCE

Full steps in the install manual

1. Choose a position away from draughts, direct sun and heat sources.
2. Isolate the supply to the heating controls and prove it dead.
3. Sink a standard 35mm deep back box and bring in the thermostat cable, plus the floor probe cable if used.
4. Wire to the zone terminals of the wiring centre per the Heatmiser diagram supplied.



07 · AT A GLANCE

Heatmiser neoStat V3 Programmable Smart Thermostat 230V

SUPPLY
230V AC

MAX SWITCHING CURRENT
3A

SCAN ME

Watch how it works and fits

Point your phone camera at the code to watch the video for this product.

DESIGN HELP, TRADE ACCOUNTS AND ORDERS

sales@maxheatufh.com **07539 499069**

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery