MaxHeatFix Low Profile Panel, 12mm Pipe

15mm clip-in panel, 600 x 600mm, pack of 10

Code: MaxHeatFix-600-10



A fast-fit, low profile pipe retention panel for 12mm pipe. The 600 x 600mm panels lock together, the pipe clips in at 150mm or 75mm centres, and the panel is just 15mm high, which suits retrofits where floor height is tight.

Key features

- ✓ 15mm high, for 10 to 12mm pipe
- ✓ Slide-and-lock edges join the panels together
- ✓ Built-in clips hold the pipe at 150mm or 75mm centres
- ✓ V-notch break lines for quick cutting, and a fixing point in every eye
- ✓ Packs of 10 cover 3.6m²

Specification

Panel size	600 x 600mm, 0.36m² per panel
Height	15mm
Pipe	12mm (takes 10 to 12mm)
Pipe centres	150mm or 75mm
Joining	Slide-and-lock snap clips
Pack	10 panels, 3.6m²

Works with

- 12mm UFH pipe
- MaxHeatFix Plus Panel for 16mm pipe
- Ultra Prime IT Multi Surface Primer
- Edge Insulation Foam Roll
- UFH manifolds

Typical heat output (W/m²) by mean water temperature

Floor finish	30°C	35°C	40°C	45°C	50°C
Tile	56.6	84.9	113.2	141.5	169.8
Vinyl or 6mm laminate	40.2	60.3	80.4	100.5	120.6
Carpet and underlay (1.5 tog)	30.0	45.0	60.0	75.0	90.0

Measured with the panel encapsulated in levelling compound. For guidance only; every system must be designed to BS EN 1264.

Specifications may change. For design help, send your plans to sales@maxheatufh.com or try MaxHeatUFH ProLoop at maxheatufh.com.