FIXINGS

Self-Adhesive Pipe Clip Rail

Interlocking rail for even pipe spacing.

A 1m self-adhesive clip rail for fixing underfloor heating pipe. The lengths interlock end to end, so you can make any run. Stick the rail down, then clip the pipe in at the spacing you need.

CODE

MH-CLIPRAIL-1M

PRODUCT



01 · IN THE BOX

What you get

- 1 x 1m clip rail

02 · YOU WILL NEED

Tools and materials

- Tape measure and marker
- Knife or snips to trim rail
- Pipe decoiler

03 · SAFETY

Before you start

- Installation should be carried out by a competent installer, in line with the system design and BS EN 1264.
- Wear gloves and eye protection when cutting pipe, handling metal plates or using hand tools.
- Release system pressure and let pipework cool before cutting into or disturbing any filled pipe.

04 · INSTALLATION

Fit it in 7 steps.

1. Make sure the floor is clean and dry, with the membrane, edge insulation and floor insulation in place.
2. Plan the rail lines from the pipe layout: run them at right angles to the pipe, about every 1 to 1.2m.
3. **Peel the backing and press each rail down firmly.** Clip lengths together end to end for longer runs.
4. Starting at the manifold flow bar, lay each loop into the rail clips at the design centres.
5. On tight bends or between rails, hold the pipe down with individual pipe clips.
6. Return to the manifold return bar and note the loop length and room on the manifold tag.
7. Repeat for every loop until the area is evenly covered.

05 · TESTING AND COMMISSIONING

Test, check, then hand over

- ☑ Fill and flush each loop one at a time, vent the air, then raise the system to 6 bar with a test pump.
- ☑ Hold 6 bar for 1 hour. A small drop can come from water temperature change; a leak usually shows within the hour.
- ☑ Have the test witnessed and signed off, and keep the pipe under pressure while the screed is laid.

06 · CARE AND MAINTENANCE

Keep it working

- Press any lifting rail back down before screeding.

07 · QUESTIONS

Asked by installers

Can I join lengths together?

Yes. The 1m lengths interlock, so you can run them end to end.

Do I need screws or staples?


No. The rail has a self-adhesive backing.

08 · WORKS WITH

Parts that fit with it



High Grip Barbed Pipe Clips for tacker systems



Reflective Aluminium Foil Insulation Roll



Pipe Decoiler

ALSO WORKS WITH

UFH pipe

09 · JOB RECORD

Fill in on site, keep for the handover

Site / room

Installed by

Date

Test result

Notes

SCAN ME

Watch how it works and fits

Point your phone camera at the code to watch the video.

QUESTIONS ON SITE?

sales@maxheatufh.com **07539 499069**

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery