UFH Non-Mixing Pump Set with Wilo A-Rated 6m Pump

Heat pump pack, Wilo 6m pump

Code: MH-NM-WILO6



A pre-assembled non-mixing pump set with a Wilo A-rated 6m-head pump and its power cable. It suits manifolds fed by a heat pump or other low-temperature source, where the flow is already at floor temperature, typically below 50 to 55°C.

Key features

- ✓ No blending valve, so nothing holds back a low heat pump flow temperature
- ✓ Built-in non-return valve in the flow elbow for easy filling
- ✓ Side or bottom primary entry, left- or right-hand fitting
- ✓ Temperature gauge fitted
- ✓ Wilo A-rated 6m pump, power cable supplied

Works with

- Heat pump connection
- Dualmix Stainless Steel Manifold Assembly
- 2-Wire Thermal Actuators 230V
- Wilo Replacement Pump Power Cable

Specification

Mixing	None (no blending valve)
Rating	Up to about 20kW / 250m² of floor
Pressure	10 bar max static, 3 bar max differential
Max temperature	95°C
Manifold connections	2 x 1" BSP male swivel joints, O-ring sealed
Primary connections	2 x 3/4" BSP female
Primary entry	Side or bottom
Handing	Left or right hand
Body	Nickel-plated brass, 4-way deflector plate
Pump	Wilo A-rated, 6m head, cable included

Specifications may change. For design help, send your plans to sales@maxheatufh.com or try MaxHeatUFH ProLoop at maxheatufh.com.