PUMPS & CONTROLS

Wilo A-Rated UFH Circulating Pump 6m Head

6m head, 130mm, cable included.

A Wilo A-rated high-efficiency circulator with a 6m maximum head, for UFH manifolds and domestic heating circuits. It comes with its power cable and is a direct replacement for the pump on our UFH pump packs.

CODE

MH-PUMP-WILO6

PRODUCT



01 · IN THE BOX

What you get

- Pump
- Power cable

02 · YOU WILL NEED

Tools and materials

- Spanners for 1½" unions
- New union gaskets
- Screwdriver

03 · SAFETY

Before you start

- Isolate the electrical supply before working on a pump, actuator or valve head. A qualified electrician makes the final connection, to BS 7671.
- Close the isolating valves or drain down, and release the pressure, before opening any joint.
- Pumps, valves and pipework can be hot. Let the system cool before you handle them.

04 · INSTALLATION

Fit it in 5 steps.

1. **Isolate the power.** Close the valves on both sides of the old pump, or drain down, before taking it out.
2. Fit the pump with new gaskets, with the arrow on the body pointing the way the water flows.
3. Tighten the union nuts evenly.
4. A qualified electrician connects the power cable, to BS 7671.
5. Fill and vent the system, then choose the pump setting.

05 · TESTING AND COMMISSIONING

Test, check, then hand over

- [x] Check the pump runs quietly and both flow and return warm up.

06 · CARE AND MAINTENANCE

Keep it working

- Check settings and fault codes against the Wilo instructions for your pump model.

07 · QUESTIONS

Asked by installers

Will it replace the pump on my MaxHeatUFH pump pack?

Yes. It fits as a direct replacement on our UFH pump packs and other 130mm pump positions.

Is the cable included?

Yes, it comes with its power cable. A replacement cable is also available separately.

08 · WORKS WITH

Parts that fit with it



Wilo Replacement Pump Power Cable if you need a spare



Blending Valve Pump Pack with Wilo 6m Pump



UFH Manifold Blending Valve 20 to 55°C (Valve Only) or UFH Non-Mixing Pump Set (No Pump) to fit your own pump



UFH Non-Mixing Pump Set (No Pump)

ALSO WORKS WITH

UFH Manifold Blending Valve Pump Pack with Wilo 6m Pump | UFH Manifold Blending Valve 20 to 55°C (Valve Only)

09 · JOB RECORD

Fill in on site, keep for the handover

Site / room

Installed by

Date

Test result

Notes

SCAN ME

Watch how it works and fits

Point your phone camera at the code to watch the video.

QUESTIONS ON SITE?

sales@maxheatufh.com **07539 499069**

WEB
maxheatufh.com

DELIVERY
Order by 12pm for next working day delivery